


1. Product and Company Identification

Product Name Super Iron Out Outdoor
CAS # Mixture
Product use Rust Stain Remover
Manufacturer Iron Out dba Summit Brands
 7201 Engle Road
 Fort Wayne, IN 46804-5875 US
 Phone: 260-483-2519
 Emergency Phone: 1-800-424-9300 (CHEMTREC)

LEGEND HMIS/NFPA	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

Health	/ 3
Flammability	0
Physical Hazard	0
Personal Protection	C



2. Hazards Identification

Emergency overview DANGER -- CORROSIVE

Potential short term health effects

Routes of exposure Eye, Skin contact, Inhalation, Ingestion.

Eyes Causes chemical burns. May cause blindness.

Skin Causes chemical burns.

Inhalation May cause respiratory tract irritation.

Ingestion Harmful if swallowed. May cause chemical burns to mouth, throat and stomach.

Target organs Eyes. Mucous membranes. Skin.

Chronic effects Prolonged or repeated exposure to dilutions can cause drying, defatting and dermatitis.

Signs and symptoms The product causes burns of eyes, skin and mucous membranes.

OSHA Regulatory Status This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Potential environmental effects This product has not been tested.

3. Composition / Information on Ingredients

Ingredient(s)	CAS #	Percent
Oxalic acid	6153-56-6	7 - 13

4. First Aid Measures

First aid procedures

Eye contact Immediately flush with cool water. Remove contact lenses, if applicable, and continue flushing for 15 minutes. Obtain medical attention immediately.

Skin contact Immediately flush with cool water for 15 minutes while removing contaminated clothing and shoes. Discard or wash well before reuse. Obtain medical attention if irritation persists.

Inhalation If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.

Ingestion Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious, or is convulsing. Obtain medical attention.

General advice

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

5. Fire Fighting Measures

Flammable properties	Not flammable by WHMIS/OSHA criteria.
Extinguishing media	
Suitable extinguishing media	Dry chemical. Water spray. Alcohol foam. Carbon dioxide.
Unsuitable extinguishing media	Not available
Protection of firefighters	
Specific hazards arising from the chemical	Not available
Protective equipment for firefighters	Firefighters should wear full protective clothing including self contained breathing apparatus.
Hazardous combustion products	May include and are not limited to: Oxides of carbon.
Explosion data	
Sensitivity to mechanical impact	Not available
Sensitivity to static discharge	Not available

6. Accidental Release Measures

Personal precautions	Keep unnecessary personnel away. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak.
Environmental precautions	Do not contaminate water.
Methods for containment	Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas.
Methods for cleaning up	Before attempting clean up, refer to hazard data given above. Small spills may be absorbed with non-reactive absorbent and placed in suitable, covered, labelled containers. Prevent large spills from entering sewers or waterways. Contact emergency services and supplier for advice. Never return spills in original containers for re-use.

7. Handling and Storage

Handling	Use good industrial hygiene practices in handling this material. Do not get this material in your eyes, on your skin, or on your clothing.
Storage	Keep out of the reach of children. Store in a closed container away from incompatible materials.

8. Exposure Controls / Personal Protection

Exposure limits

Ingredient(s)	Exposure Limits
Oxalic acid	ACGIH-TLV TWA: 1 mg/m ³ STEL: 2 mg/m ³ OSHA-PEL TWA: 1 mg/m ³

Engineering controls	Use only under good ventilation conditions or with respiratory protection.
Personal protective equipment	
Eye / face protection	Wear chemical goggles.
Hand protection	Rubber gloves. Confirm with a reputable supplier first.
Skin and body protection	As required by employer code. Rubber apron recommended.
Respiratory protection	Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.
General hygiene considerations	Use good industrial hygiene practices in handling this material. When using do not eat or drink. Wash hands before breaks and immediately after handling the product.

9. Physical and Chemical Properties

Appearance	Clear.
Color	Colorless
Form	Liquid
Odor	Odorless
Odor threshold	Not available
Physical state	Liquid
pH	<1.0
Melting point	Not available
Freezing point	Not available
Boiling point	Not available
Pour point	Not available
Evaporation rate	Not available
Flash point	Not available
Auto-ignition temperature	Not available
Flammability limits in air, lower, % by volume	Not available
Flammability limits in air, upper, % by volume	Not available
Vapor pressure	Not available
Vapor density	Not available
Specific gravity	1.05
Octanol/water coefficient	Not available
Percent volatile	Not available

10. Stability and Reactivity

Reactivity	This product may react with oxidizing agents.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Chemical stability	Stable under recommended storage conditions.
Conditions to avoid	Do not mix with other chemicals.
Incompatible materials	Oxidizers. Caustics.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon.

11. Toxicological Information

Component analysis - LC50

Ingredient(s)	LC50
Oxalic acid	Not available

Component analysis - Oral LD50

Ingredient(s)	LD50
Oxalic acid	375 mg/kg rat

Effects of acute exposure

Eye	Causes chemical burns. May cause blindness.
Skin	Causes chemical burns.
Inhalation	May cause respiratory tract irritation.
Ingestion	Harmful if swallowed. May cause chemical burns to mouth, throat and stomach.
Sensitization	Non-hazardous by WHMIS/OSHA criteria.
Chronic effects	Non-hazardous by WHMIS/OSHA criteria.
Carcinogenicity	Not classified or listed by IARC, NTP, OSHA and ACGIH.
Mutagenicity	Non-hazardous by WHMIS/OSHA criteria.
Reproductive effects	Non-hazardous by WHMIS/OSHA criteria.
Teratogenicity	Non-hazardous by WHMIS/OSHA criteria.

Name of Toxicologically Synergistic Products Not available

12. Ecological Information

Ecotoxicity	Not available
Persistence / degradability	Not available
Bioaccumulation / accumulation	Not available
Mobility in environmental media	Not available
Environmental effects	Not available
Aquatic toxicity	Not available
Partition coefficient	Not available
Chemical fate information	Not available
Other adverse effects	Not available

13. Disposal Considerations

Disposal instructions	Review federal, state/provincial, and local government requirements prior to disposal.
Waste from residues / unused products	Not available
Contaminated packaging	Not available

14. Transport Information

U.S. Department of Transportation (DOT)

Basic shipping requirements:

Proper shipping name	Corrosive liquid, acidic, organic, n.o.s. (ETHANEDIOIC ACID, DIHYDRATE)
Hazard class	8
UN number	UN3265
Packing group	III
Additional information:	
Special provisions	IB3, T7, TP1, TP28
Packaging exceptions	154
ERG number	153



Transportation of Dangerous Goods (TDG - Canada)

Basic shipping requirements:

Proper shipping name	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (ETHANEDIOIC ACID, DIHYDRATE)
Hazard class	8
UN number	UN3265
Packing group	III
Additional information:	
Special provisions	16



15. Regulatory Information

Canadian federal regulations	This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.
WHMIS status	Controlled

WHMIS classification

Class E - Corrosive Material

WHMIS labeling



Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

US Federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

CERCLA (Superfund) reportable quantity

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Clean Air Act (CAA) Not available

Clean Water Act (CWA) Not available

State regulations This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

U.S. - Pennsylvania - RTK (Right to Know) List

Oxalic acid 6153-56-6 Present

U.S. - Rhode Island - Hazardous Substance List

Oxalic acid 6153-56-6 Flammable

Inventory name

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

Disclaimer Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date 19-Jan-2011

Effective date 01-Apr-2011

Expiry date 01-Apr-2014

Prepared by Dell Tech Laboratories Ltd. (519) 858-5021

Other information For an updated MSDS, please contact the supplier/manufacturer listed on the first page of the document.